

www.pfcstore.com - 763-425-7890 / 800-328-2350



## GOULDS DUPLEX CONTROL PANEL NEMA 4, 3 PHASE, SEAL FAIL, AMP RATING 16 - 20

Voltage 208/230/460/575 |  
Estimated delivery is 5 to 6 weeks

Special duplex Mini CAS seal fail  
and high temperature circuit for  
use on only three phase 15/20GD,  
15/20GX, 1GA/2GA, GV Plus and  
Impact pumps.



---

**SKU:** CDD31620P

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Goulds Control Panels](#)

**Part Number** CDD31620P

## PRODUCT DESCRIPTION

### Gould Duplex Control Panels, indoor Duplex Wastewater Disconnect Style Panels

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

## STANDARD FEATURES

- NEMA 1 enclosure
- Pump run light(s)
- Pump H-O-A switches
- High level alarm circuit
- Automatic alarm reset on simplex panels
  - Manual alarm reset on duplex panels
  - Flashing alarm light
- Auxiliary high level (dry) alarm contacts
  - Electronic alternator on duplex panels
- Terminal strip for all external connections
  - Dual power feed for control circuit
- Duplex panels only: Alternator selector switch allows a choice of automatic alternation or operation of only pump 1 or pump 2. Typically used if one pump is down for maintenance.
- Duplex panels only: Lag pump start delay built-in. Delays starting lag pump for 5 seconds if both pumps attempt to start simultaneously as after a power outage.

## THREE PHASE

- Class 14 NEMA rated three phase starters
- Solid state adjustable ESP100 Class 10 overloads
  - Built-in automatic phase loss protection
  - Transformer for 115 volt control circuit

**Estimated delivery is 5 to 6 weeks**

[Technical Brochure](#)

## ADDITIONAL INFORMATION

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

<b>Weight</b>	40 lbs
<b>Dimensions</b>	20 × 10 × 24 in
<b>Enclosure Type</b>	<u>IP21 = NEMA 1</u>
<b>Full Load Amps</b>	<u>16-20</u>
<b>Phase</b>	<u>3</u>

Voltage 208/230/460/575 | Estimated delivery is 5 to 6 weeks

Special duplex Mini CAS seal fail and high temperature circuit for use on only three phase 15/20GD, 15/20GX, 1GA/2GA, GV Plus and Impact pumps.