

www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS DUPLEX CONTROL PANEL NEMA4X, 3 PHASE, AMP RATING 20 -25

Voltage 208/230/460/575 | Estimated delivery is 5 to 6 weeks | NOTE: NEMA 4X panel selections are dead front with an inner door



SKU: CDD32025 Stock: Out of stock contact us for lead time Categories: <u>Goulds Control Panels</u>

Part Number CDD32025

PRODUCT DESCRIPTION

Gould Duplex Control Panels, Outdoor Duplex Wastewater Disconnect Style Panels

STANDARD FEATURES

- NEMA 4X enclosure
 - Pump run light(s)
- Pump H-O-A switches

Page: 1

PFC eStore

Pumps, Filters & Controls store with B2B solution

August 20, 2025



www.pfcestore.com - 763-425-7890 / 800-328-2350

- High level alarm circuit
- Automatic alarm reset on simplex panels
 - Manual alarm reset on duplex panels
 Flashing alarm light
- Auxiliary high level (dry) alarm contacts
- Electronic alternator on duplex panels
- Terminal strip for all external connections
 - Dual power feed for control circuit
- Duplex panels only: Alternator selector switch allows a choice of automatic alternation or operation of only pump 1 or pump 2. Typically used if one pump is down for maintenance.
- Duplex panels only: Lag pump start delay built-in. Delays starting lag pump for 5 seconds if both pumps attempt to start simultaneously as after a power outage.

THREE PHASE

- Class 14 NEMA rated three phase starters
- Solid state adjustable ESP100 Class 10 overloads
 - Built-in automatic phase loss protection
 - Transformer for 115 volt control circuit

Estimated delivery is 5 to 6 weeks

Technical Brochure

ADDITIONAL INFORMATION

Weight Dimensions Enclosure Type

65 lbs 20 × 10 × 24 in

<u> IP66 = NEMA 4X</u>



www.pfcestore.com - 763-425-7890 / 800-328-2350

Full Load Amps	<u>20-25</u>
Phase	<u>3</u>