

www.pfcstore.com - 763-425-7890 / 800-328-2350



GOULDS E-HMX PUMP, 316SS, 200-240 VOLTS, 3 PHASE, 15HMX02N30TM5BQE

Best Efficiency Point: 90 GPM @
105 FTH | IP55, NEMA 4 enclosure |
Multi-pump linking: up to 8 pumps

Control Modes include: actuator,
constant pressure, proportional
pressure, proportional quadratic
pressure, constant flow, constant
temperature, constant level



SKU: 15HMX02N30TM5BQE

Stock: Out of stock contact us for
lead time

Categories: [Goulds e-HMX Pumps](#)

PRODUCT DESCRIPTION

Goulds e-HMX Smart Pump

www.pfcstore.com - 763-425-7890 / 800-328-2350



For a full list of features and specifications of the hydrovar X motor, please scan the QR code below to see more documentation.



Typical Delivery is 2 to 3 weeks, contact us for updated delivery

[Curve & Specs](#)

[Technical Specs](#)

[Manual](#)

ADDITIONAL INFORMATION

Weight	70 lbs
Dimensions	28 × 16 × 17 in
Best Efficiency Point	<u>90 GPM @ 108 FTH</u>
Voltage	<u>200-240</u>

Best Efficiency Point: 90 GPM @ 105 FTH | IP55, NEMA 4 enclosure | Multi-pump linking: up to 8 pumps

Control Modes include: actuator, constant pressure, proportional pressure, proportional quadratic pressure, constant flow, constant temperature, constant level