

www.pfcstore.com - 763-425-7890 / 800-328-2350



**GOULDS E-HMX PUMP,
316SS, 380-480 VOLTS, 3
PHASE,
3HMX14N30TM6BQE**

Best Efficiency Point: 17 GPM @
416 FTH | IP55, NEMA 4 enclosure |
Multi-pump linking: up to 8 pumps

Control Modes include: actuator,
constant pressure, proportional
pressure, proportional quadratic
pressure, constant flow, constant
temperature, constant level



SKU: 3HMX14N30TM6BQE

Stock: Out of stock contact us for
lead time

Categories: [Goulds e-HMX Pumps](#)

PRODUCT DESCRIPTION

Goulds e-HMX Smart Pump

www.pfcstore.com - 763-425-7890 / 800-328-2350



For a full list of features and specifications of the hydrovar X motor, please scan the QR code below to see more documentation.



Typical Delivery is 2 to 3 weeks, contact us for updated delivery

[Curve & Specs](#)

[Technical Specs](#)

[Manual](#)

ADDITIONAL INFORMATION

Weight	71 lbs
Dimensions	34 × 16 × 17 in
Best Efficiency Point	<u>17 GPM @ 416 FTH</u>
Voltage	<u>380-480</u>

Best Efficiency Point: 17 GPM @ 416 FTH | IP55, NEMA 4 enclosure | Multi-pump linking: up to 8 pumps

Control Modes include: actuator, constant pressure, proportional pressure, proportional quadratic pressure, constant flow, constant temperature, constant level