

www.pfcstore.com - 763-425-7890 / 800-328-2350



**GOULDS E-HMX PUMP,  
316SS, 380-480 VOLTS, 3  
PHASE,  
5HMX09N30TM6BQE**

Best Efficiency Point: 33 GPM @  
260 FTH | IP55, NEMA 4 enclosure |  
Multi-pump linking: up to 8 pumps

Control Modes include: actuator,  
constant pressure, proportional  
pressure, proportional quadratic  
pressure, constant flow, constant  
temperature, constant level



---

**SKU:** 5HMX09N30TM6BQE

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Goulds e-HMX Pumps](#)

## PRODUCT DESCRIPTION

### Goulds e-HMX Smart Pump

www.pfcstore.com - 763-425-7890 / 800-328-2350



For a full list of features and specifications of the hydrovar X motor, please scan the QR code below to see more documentation.



**Typical Delivery is 2 to 3 weeks, contact us for updated delivery**

[Curve & Specs](#)

[Technical Specs](#)

[Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	71 lbs
<b>Dimensions</b>	34 × 16 × 17 in
<b>Best Efficiency Point</b>	<a href="#">30 GPM @ 260 FTH</a>
<b>Voltage</b>	<a href="#">380-480</a>

Best Efficiency Point: 33 GPM @ 260 FTH | IP55, NEMA 4 enclosure | Multi-pump linking: up to 8 pumps

Control Modes include: actuator, constant pressure, proportional pressure, proportional quadratic pressure, constant flow, constant temperature, constant level