



GOULDS E-SVI COOLANT IMMERSION PUMP 304SS/CAST IRON 10SVI1515G

60 GPM @ 550 FTH | Immersion
Depth 23" | Wetted Material
304SS/Cast Iron, Car-Silcar FKM |
Motor TEPE 3/60/230-460v, 15hp |
Connection 2" NPT



SKU: 10SVI1515GK4C6S0

Stock: Out of stock contact us for
lead time

Categories: [Goulds Coolant
Pumps](#)

Part Number 10SVI1515GK4C6S0

PRODUCT DESCRIPTION

The e-SVI offers a range of shaft seals to handle high temperatures,

www.pfcstore.com - 763-425-7890 / 800-328-2350

pressures and aggressive liquids. The e-SVI's design allows the removal of the standard mechanical seal without having to remove the motor thus reducing repair time. Also available is an easy to replace pre-assembled cartridge seal configuration ensuring the seal components will never be assembled incorrectly. The inducer is a standard feature offered to allow for reliable low level pumping.

Estimated delivery 3 to 4 weeks

[Specs & Curve](#)

[Technical Brochure](#)

[Manual](#)

[Brochure](#)

ADDITIONAL INFORMATION

Weight	299 lbs
Dimensions	55 × 14 × 14 in
Best Efficiency Point	60 GPM @ 550 FTH
Length	Pump Depth 23.30"
Phase	3
Wetted Material	CAST IRON-304SS-VITON

60 GPM @ 550 FTH | Immersion Depth 23" | Wetted Material 304SS/Cast Iron, Car-Silcar FKM | Motor TEPE 3/60/230-460v, 15hp | Connection 2" NPT