

www.pfcstore.com - 763-425-7890 / 800-328-2350



GOULDS E-SVI COOLANT IMMERSION PUMP 304SS/CAST IRON 1SVI1313G

9 GPM @ 295 FTH | Immersion
Depth 13-5/16" | Wetted Material
304SS, Cast Iron, Car-Silcar FKM |
Motor TEPE 3/60/208-230-460v,
1.5hp | Connection 3/4" NPT



SKU: 1SVI1313GD4F6S0

Stock: Out of stock contact us for
lead time

Categories: [Goulds Coolant
Pumps](#)

Part Number 1SVI1313GD4F6S0

PRODUCT DESCRIPTION

The e-SVI offers a range of shaft seals to handle high temperatures,

www.pfcestore.com - 763-425-7890 / 800-328-2350

pressures and aggressive liquids. The e-SVI's design allows the removal of the standard mechanical seal without having to remove the motor thus reducing repair time. Also available is an easy to replace pre-assembled cartridge seal configuration ensuring the seal components will never be assembled incorrectly. The inducer is a standard feature offered to allow for reliable low level pumping.

Estimated delivery 3 to 4 weeks

[Specs & Curve](#)

[Technical Brochure](#)

[Manual](#)

[Brochure](#)

ADDITIONAL INFORMATION

Weight	70 lbs
Dimensions	36 × 14 × 14 in
Best Efficiency Point	<u>9 GPM @ 295 FTH</u>
Length	<u>Pump Depth 13.4"</u>
Phase	<u>3</u>
Wetted Material	<u>CAST IRON-304SS-VITON</u>