



GOULDS E-SVI COOLANT IMMERSION PUMP 316SS 3SVI1606N

14 GPM @ 178 FTH | Immersion
Depth 15-11/16" | Wetted Material
316SS, Car-Silcar FKM | Motor TEPE
3/60/208-230-460v, 1.5hp |
Connection 1.25" NPT



SKU: 3SVI1606ND4F6S0

Stock: Out of stock contact us for
lead time

Categories: [Goulds Coolant
Pumps](#)

Part Number 3SVI1606ND4F6S0

PRODUCT DESCRIPTION

The e-SVI offers a range of shaft seals to handle high temperatures,

www.pfcestore.com - 763-425-7890 / 800-328-2350

pressures and aggressive liquids. The e-SVI's design allows the removal of the standard mechanical seal without having to remove the motor thus reducing repair time. Also available is an easy to replace pre-assembled cartridge seal configuration ensuring the seal components will never be assembled incorrectly. The inducer is a standard feature offered to allow for reliable low level pumping.

Estimated delivery 3 to 4 weeks

[Specs & Curve](#)

[Technical Brochure](#)

[Manual](#)

ADDITIONAL INFORMATION

Weight	70 lbs
Dimensions	36 × 14 × 14 in
Best Efficiency Point	<u>14 GPM @ 178 FTH</u>
Length	<u>Pump Depth 15-9/16"</u>
Phase	<u>3</u>
Wetted Material	<u>316SS-VITON</u>

14 GPM @ 178 FTH | Immersion Depth 15-11/16" | Wetted Material 316SS, Car-Silcar FKM | Motor TEPE 3/60/208-230-460v, 1.5hp | Connection 1.25" NPT