

www.pfcstore.com - 763-425-7890 / 800-328-2350



GOULDS EZ96 MAG DRIVE PROCESS PUMP, ON SALE

Brand New Pump & Motor. BEP
65GPM @ 95FTH

Liquid End, BEARING CARTRIDGE -
DUPLEX STAINLESS STEEL
(1.4517)/SILICON CARBIDE
BEARINGS, IMPELLER AND MAGNET
ASSEMBLY BALANCED TO ISO 1940
G6.3, HAST C CONTAINMENT
SHELL - DEEP DRAWN ONE PIECE
(NO WELDS). IMPELLER STAINLESS
STEEL (1.4408). PUMP 316SS.

Weg Motor, 7.5hp, 3/60/460v,
1800rpm, CLASS 1 DIV. 2
INVERTER CAPABLE

Base cast iron



SKU: EZ96 1X2-10

Stock: 1 in stock

Categories: [Inventory Sale!](#)

Model Number 3296 EZMAG

PRODUCT DESCRIPTION

- Chemical Process Pump
 - Capacities to 700 gpm (160 m³/h)
 - Heads to 620 ft (189 m)
 - Temperatures to 535°F (280°C)
 - Pressures to 275 PSIG
 - Performance Features
 - Extended Pump Life
 - Sealless design
 - Enclosed impeller
 - Silicon carbide radial and thrust bearings
 - Optional Dryguard™ bearings for dry run protection
 - Reliable flush circuit
 - Ease of Maintenance
 - Bearing Cartridge design
 - Double-back pull-out
 - Close coupled option on S group
 - ANSI B73.1 dimensional standards
 - No mechanical seal
 - Minimum number of parts
- Safety
- Zero emissions
 - One-piece Hastelloy C containment shell
 - Drive and driven magnet clearances protect containment shell
- Bearing Cartridge design contains bearings in case of failure
 - Adapter drain connection

[Brochure](#)

[Curve](#)

[BOM](#)

www.pfcstore.com - 763-425-7890 / 800-328-2350

Manual

ADDITIONAL INFORMATION

Weight	670 lbs
Dimensions	52 × 24 × 35 in
Manufacturer	<u>Goulds EZ96 Mag Drive</u>

Brand New Pump & Motor. BEP 65GPM @ 95FTH

Liquid End, BEARING CARTRIDGE - DUPLEX STAINLESS STEEL (1.4517)/SILICON CARBIDE BEARINGS, IMPELLER AND MAGNET ASSEMBLY BALANCED TO ISO 1940 G6.3, HAST C CONTAINMENT SHELL - DEEP DRAWN ONE PIECE (NO WELDS). IMPELLER STAINLESS STEEL (1.4408). PUMP 316SS.

Weg Motor, 7.5hp, 3/60/460v, 1800rpm, CLASS 1 DIV. 2 INVERTER CAPABLE

Base cast iron