PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

GOULDS SIMPLEX CONTROL PANEL NEMA4X, 3 PHASE, AMP RATING 4.0-6.3

Voltage 208/230/460/575 | Estimated delivery 5 to 6 weeks | NOTE: NEMA 4X panel selections are dead front with an inner door

SKU: CSD34063
Stock: Out of stock contact us for lead time
Categories: Goulds Control Panels

Part Number CSD34063

PRODUCT DESCRIPTION

Gould Simplex Control Panels, Outdoor Simplex Wastewater Disconnect Style Panels

STANDARD FEATURES

- NEMA 4X enclosure
- Pump run light(s)
- Pump H-O-A switches

• High level alarm circuit
• Automatic alarm reset on simplex panels
• Manual alarm reset on duplex panels
• Flashing alarm light
• Auxiliary high level (dry) alarm contacts
• Electronic alternator on duplex panels
• Terminal strip for all external connections
• Dual power feed for control circuit
• Duplex panels only: Alternator selector switch allows a choice of automatic alternation or operation of only pump 1 or pump 2. Typically used if one pump is down for maintenance.
• Duplex panels only: Lag pump start delay built-in. Delays starting lag pump for 5 seconds if both pumps attempt to start simultaneously as after a power outage.

THREE PHASE

• Class 14 NEMA rated three phase starters
• Solid state adjustable ESP100 Class 10 overloads
• Built-in automatic phase loss protection
• Transformer for 115 volt control circuit

Estimated delivery is 5 to 6 weeks

Technical Brochure

ADDITIONAL INFORMATION

Weight	35 lbs
Dimensions	20 × 10 × 24 in
Enclosure Type	IP66 = NEMA 4X

PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

Full Load Amps	4.0-6.3
Phase	3