PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS SUBMERSIBLE SEWAGE PUMP 3WS

Cast iron/Buna Silicon Carbide Seal | Cable STOW, 20ft Length | 1.5HP | 3 Phase | 460 Volts | 1800 RPM | 275 GPM @ 40 FTH



SKU: WS5034D3

Stock: Out of stock contact us for

lead time

Categories: Goulds Sewage

<u>Pumps</u>

Tags: Goulds Sewage Pumps Model Number WS5034D3

PRODUCT DESCRIPTION

Goulds submersible sewage pump standard silicon carbide/silicon carbide outer (lower) seals. Impeller: Cast iron, ASTM A48, Class 30, two vane semi-open, non-clog design with pump out vanes for mechanical seal protection. Dynamically balanced for smooth operation. silicon bronze impeller is an option.

Casing: Heavy duty gray cast iron, ASTM A48, Class 30. Volute type casing with 4", 125#, flanged, horizontal discharge conforming to ANSI standards. Compatible with A10-40, A10- 60 cast iron or A10-40B, A10-60B cast iron



www.pfcestore.com - 763-425-7890 / 800-328-2350

and brass (non-sparking) guide rail assembly. Goulds submersible sewagepump Dual Mechanical Seals: Silicon carbide vs. silicon carbide outer seal and ceramic vs. carbon inner seal, stainless steel metal parts, BUNA-N elastomers. Upper and lower tandem mounted shaft seals are positioned independently and are separated by an oil-filled chamber. Components: Capable of running dry without damage to components.

Estimated delivery is 3 to 4 weeks. Contact us for actual lead time

Product photo could vary from the actual product

Curve

Technical Specs

<u>Manual</u>

ADDITIONAL INFORMATION

Weight 220 lbs

Dimensions $36 \times 24 \times 24$ in

Best Efficiency Point 275 GPM @ 40 FTH

Connections 3" ANSI FLANGE

Hertz <u>60</u>

Horse Power <u>5</u>

<u>3</u>

RPM 1800

Solid Size <u>2.5"</u>

Voltage 460

Wetted Material CAST IRON-BUNA



www.pfcestore.com - 763-425-7890 / 800-328-2350