

www.pfcstore.com - 763-425-7890 / 800-328-2350



## GOULDS SUBMERSIBLE SEWAGE PUMP 3WS

Cast iron/Buna Silicon Carbide Seal  
| Cable STOW, 20ft Length | 1.5HP  
| Single Phase | 230 Volts | 1800  
RPM | 197 GPM @ 21 FTH



**SKU:** WS1512D3

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Goulds Sewage  
Pumps](#)

**Tags:** [Goulds Sewage Pumps](#)  
**Model Number** WS1512D3

## PRODUCT DESCRIPTION

Goulds submersible sewage pump standard silicon carbide/silicon carbide outer (lower) seals. Impeller: Cast iron, ASTM A48, Class 30, two vane semi-open, non-clog design with pump out vanes for mechanical seal protection. Dynamically balanced for smooth operation. silicon bronze impeller is an option.

Casing: Heavy duty gray cast iron, ASTM A48, Class 30. Volute type casing with 4", 125#, flanged, horizontal discharge conforming to ANSI standards. Compatible with A10-40, A10- 60 cast iron or A10-40B, A10-60B cast iron

www.pfcestore.com - 763-425-7890 / 800-328-2350

and brass (non-sparking) guide rail assembly. Goulds submersible sewage-pump Dual Mechanical Seals: Silicon carbide vs. silicon carbide outer seal and ceramic vs. carbon inner seal, stainless steel metal parts, BUNA-N elastomers. Upper and lower tandem mounted shaft seals are positioned independently and are separated by an oil-filled chamber.  
Components: Capable of running dry without damage to components.

Estimated delivery is 3 to 4 weeks. Contact us for actual lead time

Product photo could vary from the actual product

[Curve](#)

[Technical Specs](#)

[Manual](#)

ADDITIONAL INFORMATION

|                       |                                  |
|-----------------------|----------------------------------|
| Weight                | 220 lbs                          |
| Dimensions            | 36 × 24 × 24 in                  |
| Best Efficiency Point | <a href="#">197 GPM @ 21 FTH</a> |
| Connections           | <a href="#">3" ANSI FLANGE</a>   |
| Hertz                 | <a href="#">60</a>               |
| Horse Power           | <a href="#">1.5</a>              |
| Phase                 | <a href="#">1</a>                |
| RPM                   | <a href="#">1800</a>             |
| Solid Size            | <a href="#">2.5"</a>             |
| Voltage               | <a href="#">230</a>              |
| Wetted Material       | <a href="#">CAST IRON-BUNA</a>   |

**[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350**