



## GOULDS SUBMERSIBLE SEWAGE PUMP 3WS

Cast iron/Buna Silicon Carbide Seal  
| Cable STOW, 20ft Length | 1.5HP  
| 3 Phase | 230 Volts | 1800 RPM |  
135 GPM @ 12 FTH



**SKU:** WS1532D3M

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Goulds Sewage  
Pumps](#)

**Model Number** WS1532D3M

## PRODUCT DESCRIPTION

Goulds submersible sewage pump standard silicon carbide/silicon carbide outer (lower) seals. Impeller: Cast iron, ASTM A48, Class 30, two vane semi-open, non-clog design with pump out vanes for mechanical seal protection.

Dynamically balanced for smooth operation. silicon bronze impeller is an option.

Casing: Heavy duty gray cast iron, ASTM A48, Class 30. Volute type casing with 4", 125#, flanged, horizontal discharge conforming to ANSI standards. Compatible with A10-40, A10- 60 cast iron or A10-40B, A10-60B cast iron

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

and brass (non-sparking) guide rail assembly. Goulds submersible sewage-pump Dual Mechanical Seals: Silicon carbide vs. silicon carbide outer seal and ceramic vs. carbon inner seal, stainless steel metal parts, BUNA-N elastomers. Upper and lower tandem mounted shaft seals are positioned independently and are separated by an oil-filled chamber.

Components: Capable of running dry without damage to components.

Estimated delivery is 3 to 4 weeks. Contact us for actual lead time

Product photo could vary from the actual product

[Curve](#)

[Technical Specs](#)

[Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	220 lbs
<b>Dimensions</b>	36 × 24 × 24 in
<b>Best Efficiency Point</b>	<a href="#">135 GPM @ 12 FTH</a>
<b>Connections</b>	<a href="#">3" ANSI FLANGE</a>
<b>Hertz</b>	<a href="#">60</a>
<b>Horse Power</b>	<a href="#">1.5</a>
<b>Phase</b>	<a href="#">3</a>
<b>RPM</b>	<a href="#">1800</a>
<b>Solid Size</b>	<a href="#">2.5"</a>
<b>Voltage</b>	<a href="#">230</a>
<b>Wetted Material</b>	<a href="#">CAST IRON-BUNA</a>

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

Cast iron/Buna Silicon Carbide Seal | Cable STOW, 20ft Length | 1.5HP | 3 Phase  
| 230 Volts | 1800 RPM | 135 GPM @ 12 FTH