

www.pfcstore.com - 763-425-7890 / 800-328-2350



GOULDS SUBMERSIBLE SEWAGE PUMP 3WS

Cast iron/Buna Silicon Carbide Seal
| Cable STOW, 20ft Length | 1.5HP
| 3 Phase | 230 Volts | 1800 RPM |
275 GPM @ 40 FTH



SKU: WS5032D3

Stock: Out of stock contact us for
lead time

Categories: [Goulds Sewage
Pumps](#)

Tags: [Goulds Sewage Pumps](#)
Model Number WS5032D3

PRODUCT DESCRIPTION

Goulds submersible sewage pump standard silicon carbide/silicon carbide outer (lower) seals. Impeller: Cast iron, ASTM A48, Class 30, two vane semi-open, non-clog design with pump out vanes for mechanical seal protection. Dynamically balanced for smooth operation. silicon bronze impeller is an option.

Casing: Heavy duty gray cast iron, ASTM A48, Class 30. Volute type casing with 4", 125#, flanged, horizontal discharge conforming to ANSI standards. Compatible with A10-40, A10- 60 cast iron or A10-40B, A10-60B cast iron

www.pfcestore.com - 763-425-7890 / 800-328-2350

and brass (non-sparking) guide rail assembly. Goulds submersible sewage-pump Dual Mechanical Seals: Silicon carbide vs. silicon carbide outer seal and ceramic vs. carbon inner seal, stainless steel metal parts, BUNA-N elastomers. Upper and lower tandem mounted shaft seals are positioned independently and are separated by an oil-filled chamber.
Components: Capable of running dry without damage to components.

Estimated delivery is 3 to 4 weeks. Contact us for actual lead time

Product photo could vary from the actual product

[Curve](#)

[Technical Specs](#)

[Manual](#)

ADDITIONAL INFORMATION

Weight	220 lbs
Dimensions	36 × 24 × 24 in
Best Efficiency Point	275 GPM @ 40 FTH
Connections	3" ANSI FLANGE
Hertz	60
Horse Power	5
Phase	3
RPM	1800
Solid Size	2.5"
Voltage	230
Wetted Material	CAST IRON-BUNA

www.pfcestore.com - 763-425-7890 / 800-328-2350