




GOULDS SUBMERSIBLE SEWAGE PUMP 4WS

Cast iron/Buna Silicon Carbide Seal
| Cable STOW, 20ft Length | 1.5HP
| Single Phase | 230 Volts | 1800
RPM | 314 GPM @ 15 FTH



SKU: WS1512D4

Stock: Out of stock contact us for lead time

Categories: [Gooulds Sewage Pumps](#)

Model Number WS1512D4

PRODUCT DESCRIPTION

Gooulds submersible sewage pump standard silicon carbide/silicon carbide outer (lower) seals. Impeller: Cast iron, ASTM A48, Class 30, two vane semi-open, non-clog design with pump out vanes for mechanical seal protection.

Dynamically balanced for smooth operation. silicon bronze impeller is an option.

Casing: Heavy duty gray cast iron, ASTM A48, Class 30. Volute type casing with 4", 125#, flanged, horizontal discharge conforming to ANSI standards. Compatible with A10-40, A10- 60 cast iron or A10-40B, A10-60B cast iron

www.pfcstore.com - 763-425-7890 / 800-328-2350

and brass (non-sparking) guide rail assembly. Goulds submersible sewage-pump Dual Mechanical Seals: Silicon carbide vs. silicon carbide outer seal and ceramic vs. carbon inner seal, stainless steel metal parts, BUNA-N elastomers. Upper and lower tandem mounted shaft seals are positioned independently and are separated by an oil-filled chamber.
Components: Capable of running dry without damage to components.

Estimated delivery is 3 to 4 weeks. Contact us for actual lead time

Product photo could vary from the actual product

[Curve](#)

[Technical Specs](#)

[Manual](#)

ADDITIONAL INFORMATION

Weight	220 lbs
Dimensions	36 × 24 × 24 in
Best Efficiency Point	314 GPM @ 15 FTH
Connections	4" ANSI FLANGE
Hertz	60
Horse Power	1.5
Phase	1
RPM	1800
Solid Size	3"
Voltage	230
Wetted Material	CAST IRON-BUNA

www.pfcestore.com - 763-425-7890 / 800-328-2350

Cast iron/Buna Silicon Carbide Seal | Cable STOW, 20ft Length | 1.5HP | Single Phase | 230 Volts | 1800 RPM | 314 GPM @ 15 FTH