

www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS SUBMERSIBLE SEWAGE PUMP 4WS

Cast iron/Buna Silicon Carbide Seal | Cable STOW, 20ft Length | 1.5HP | 3 Phase | 460 Volts | 1800 RPM | 314 GPM @ 15 FTH



SKU: WS1534D4
Stock: Out of stock contact us for lead time
Categories: Goulds Sewage
Pumps
Tags: Goulds Sewage Pumps
Model Number WS1534D4

PRODUCT DESCRIPTION

Goulds submersible sewage pump standard silicon carbide/silicon carbide outer (lower) seals. Impeller: Cast iron, ASTM A48, Class 30, two vane semiopen, non-clog design with pump out vanes for mechanical seal protection. Dynamically balanced for smooth operation. silicon bronze impeller is an option.

Casing: Heavy duty gray cast iron, ASTM A48, Class 30. Volute type casing with 4", 125#, flanged, horizontal discharge conforming to ANSI standards. Compatible with A10-40, A10- 60 cast iron or A10-40B, A10-60B cast iron



www.pfcestore.com - 763-425-7890 / 800-328-2350

and brass (non-sparking) guide rail assembly. Goulds submersible sewagepump Dual Mechanical Seals: Silicon carbide vs. silicon carbide outer seal and ceramic vs. carbon inner seal, stainless steel metal parts, BUNA-N elastomers. Upper and lower tandem mounted shaft seals are positioned independently and are separated by an oil-filled chamber. Components: Capable of running dry without damage to components.

Estimated delivery is 3 to 4 weeks. Contact us for actual lead time

Product photo could vary from the actual product

<u>Curve</u> <u>Technical Specs</u> Manual

ADDITIONAL INFORMATION

Weight	220 lbs
Dimensions	36 × 24 × 24 in
Best Efficiency Point	<u>314 GPM @ 15 FTH</u>
Connections	<u>4" ANSI FLANGE</u>
Hertz	<u>60</u>
Horse Power	<u>1.5</u>
Phase	<u>3</u>
RPM	<u>1800</u>
Solid Size	<u>3"</u>
Voltage	<u>460</u>
Wetted Material	CAST IRON-BUNA



www.pfcestore.com - 763-425-7890 / 800-328-2350