PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

# GOULDS SUBMERSIBLE SEWAGE PUMP 4WS

Cast iron/Buna Silicon Carbide Seal | Cable STOW, 20ft Length | 1.5HP | Single Phase | 230 Volts | 1800 RPM | 257 GPM @ 11 FTH

**SKU:** WS1512D4M
**Stock:** Out of stock contact us for lead time
**Categories:** Goulds Sewage Pumps
**Tags:** Goulds Sewage Pumps
**Model Number** WS1512D4M

## PRODUCT DESCRIPTION

Goulds submersible sewage pump standard silicon carbide/silicon carbide outer (lower) seals. Impeller: Cast iron, ASTM A48, Class 30, two vane semi-open, non-clog design with pump out vanes for mechanical seal protection. Dynamically balanced for smooth operation. silicon bronze impeller is an option.

Casing: Heavy duty gray cast iron, ASTM A48, Class 30. Volute type casing with 4″, 125#, flanged, horizontal discharge conforming to ANSI standards. Compatible with A10-40, A10- 60 cast iron or A10-40B, A10-60B cast iron

and brass (non-sparking) guide rail assembly. Goulds submersible sewage-pump Dual Mechanical Seals: Silicon carbide vs. silicon carbide outer seal and ceramic vs. carbon inner seal, stainless steel metal parts, BUNA-N elastomers. Upper and lower tandem mounted shaft seals are positioned independently and are separated by an oil-filled chamber. Components: Capable of running dry without damage to components.

Estimated delivery is 3 to 4 weeks. Contact us for actual lead time

Product photo could vary from the actual product

Curve

Technical Specs

Manual

## ADDITIONAL INFORMATION

| | |
|---|---|
| **Weight** | 220 lbs |
| **Dimensions** | 36 × 24 × 24 in |
| **Best Efficiency Point** | 257 GPM @ 11 FTH |
| **Connections** | 4" ANSI FLANGE |
| **Hertz** | 60 |
| **Horse Power** | 1.5 |
| **Phase** | 1 |
| **RPM** | 1800 |
| **Solid Size** | 3" |
| **Voltage** | 230 |
| **Wetted Material** | CAST IRON-BUNA |

PFC eSTORE
Clear Solutions Technology Company

**www.pfcestore.com - 763-425-7890 / 800-328-2350**