

www.pfcestore.com - 763-425-7890 / 800-328-2350

## GOULDS WASTEWATER PUMP DUAL SEAL THE 2ED SERIES WITH SEAL SENSOR, 1-PHASE

BEP 40 GPM @ 42 FTH | Material  
Cast Iron - Buna | 20ft Cord |  
Voltage 208v | Horsepower 3/4hp |  
Max Temp 104°F



**SKU:** 2ED51D8CA

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Goulds Wastewater  
Pumps](#)

**Part Number** 2ED51D8CA

## PRODUCT DESCRIPTION

Goulds wastewater pump. Impeller: Cast iron, semi-open, non-clog with pump-out vanes for mechanical seal protection. Balanced for smooth operation. Silicon bronze impeller available as an option.

Casing: Cast iron volute type for maximum efficiency. 2" NPT discharge.  
Dual Mechanical Seals

- Lower: SILICON CARBIDE VS. SILICON CARBIDE sealing faces. Stainless

www.pfcestore.com - 763-425-7890 / 800-328-2350

steel metal parts, BUNA-N elastomers.

- Upper: CARBON VS. CERAMIC sealing faces. Stainless steel metal parts, BUNA-N elastomers.

Seal Sensor Probe: Located in oil-filled chamber. If pumpage should begin to leak past lower seal it indicates to pump control panel a fault has occurred. Requires optional Seal Fail Circuit in the control panel.

Shaft: Corrosion resistant, stainless steel. Threaded design. Locknut on all models to guard against component damage on accidental reverse rotation.

Fasteners: 300 series stainless steel.

Capable of running dry without damage to components.  
Designed for continuous operation when fully submerged.

**Estimated delivery is 3 weeks**

[Specs & Curve](#)

[Goulds Technical Brochure](#)

ADDITIONAL INFORMATION

Weight	98 lbs
Dimensions	26 × 20 × 16 in
Best Efficiency Point	<a href="#">40 GPM @ 42 FTH</a>
Connections	<a href="#">2" NPT</a>
Phase	<a href="#">1</a>
Solid Size	<a href="#">.75</a>
Voltage	<a href="#">208</a>
Wetted Material	<a href="#">CAST IRON-BUNA</a>

**[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350**