PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

# GOULDS WASTEWATER PUMP DUAL SEAL THE 2ED SERIES WITH SEAL SENSOR, 3-PHASE

BEP 55 GPM @ 48 FTH | Material Cast Iron - Buna | 20ft Cord | Voltage 230v | Horsepower 1-hp | Max Temp 104°F

**SKU:** 2ED51E3BA
**Stock:** Out of stock contact us for lead time
**Categories:** Goulds Wastewater Pumps

**Part Number** 2ED51E3BA

## PRODUCT DESCRIPTION

Goulds wastewater pump.  Impeller: Cast iron, semi-open, non-clog with pump-out vanes for mechanical seal protection. Balanced for smooth operation. Silicon bronze impeller available as an option.
Casing: Cast iron volute type for maximum efficiency. 2" NPT discharge.
Dual Mechanical Seals
• Lower: SILICON CARBIDE VS. SILICON CARBIDE sealing faces. Stainless

steel metal parts, BUNA-N elastomers.
• Upper: CARBON VS. CERAMIC sealing faces. Stainless steel metal parts, BUNA-N elastomers.
Seal Sensor Probe: Located in oil-filled chamber. If pumpage should begin to leak past lower seal it indicates to pump control panel a fault has occurred. Requires optional Seal Fail Circuit in the control panel.
Shaft: Corrosion resistant, stainless steel. Threaded design. Locknut on all models to guard against component damage on accidental reverse rotation.
Fasteners: 300 series stainless steel.
Capable of running dry without damage to components.
Designed for continuous operation when fully submerged.

**Estimated delivery is 3 weeks**

Specs & Curve

Goulds Technical Brochure

## ADDITIONAL INFORMATION

| | |
|---|---|
| **Weight** | 98 lbs |
| **Dimensions** | 26 × 20 × 16 in |
| **Best Efficiency Point** | 55 GPM @ 48 FTH |
| **Connections** | 2" NPT |
| **Phase** | 3 |
| **Solid Size** | .75 |
| **Voltage** | 230 |
| **Wetted Material** | CAST IRON-BUNA |

PFC eSTORE
Clear Solutions Technology Company

**www.pfcestore.com - 763-425-7890 / 800-328-2350**