PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS WASTEWATER PUMP DUAL SEAL THE 2ED SERIES WITH SEAL SENSOR, 3-PHASE

BEP 55 GPM @ 68 FTH | Material Cast Iron - Buna | 20ft Cord | Voltage 460v | Horsepower 1.50 hp | Max Temp 104°F



SKU: 2ED51F4GA

Stock: Out of stock contact us for

lead time

Categories: Goulds Wastewater

<u>Pumps</u>

Part Number 2ED51F4GA

PRODUCT DESCRIPTION

Goulds wastewater pump. Impeller: Cast iron, semi-open, non-clog with pump-out vanes for mechanical seal protection. Balanced for smooth operation. Silicon bronze impeller available as an option.

Casing: Cast iron volute type for maximum efficiency. 2" NPT discharge.

Dual Mechanical Seals

• Lower: SILICON CARBIDE VS. SILICON CARBIDE sealing faces. Stainless



www.pfcestore.com - 763-425-7890 / 800-328-2350

steel metal parts, BUNA-N elastomers.

• Upper: CARBON VS. CERAMIC sealing faces. Stainless steel metal parts, BUNA-N elastomers.

Seal Sensor Probe: Located in oil-filled chamber. If pumpage should begin to leak past lower seal it indicates to pump control panel a fault has occurred. Requires optional Seal Fail Circuit in the control panel.

Shaft: Corrosion resistant, stainless steel. Threaded design. Locknut on all models to guard against component damage on accidental reverse rotation.

Fasteners: 300 series stainless steel.
Capable of running dry without damage to components.
Designed for continuous operation when fully submerged.

Estimated delivery is 3 weeks

Specs & Curve

Goulds Technical Brochure

ADDITIONAL INFORMATION

Weight 100 lbs

Dimensions $26 \times 20 \times 16 \text{ in}$

Best Efficiency Point 55 GPM @ 68 FTH

Connections 2" NPT

Phase 3

Solid Size .75

Voltage 460

Wetted Material <u>CAST IRON-BUNA</u>



www.pfcestore.com - 763-425-7890 / 800-328-2350