PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

GOULDS WASTEWATER PUMP DUAL SEAL THE 2ED SERIES WITH SEAL SENSOR, 3-PHASE

BEP 30 GPM @ 40 FTH | Material Cast Iron - Buna | 20ft Cord | Voltage 575v | Horsepower 1/2hp | Max Temp 104°F

SKU: 2ED51C5HA
Stock: Out of stock contact us for lead time
Categories: Goulds Wastewater Pumps

Part Number 2ED51C5HA

PRODUCT DESCRIPTION

Goulds wastewater pump. Impeller: Cast iron, semi-open, non-clog with pump-out vanes for mechanical seal protection. Balanced for smooth operation. Silicon bronze impeller available as an option.
Casing: Cast iron volute type for maximum efficiency. 2" NPT discharge.
Dual Mechanical Seals
• Lower: SILICON CARBIDE VS. SILICON CARBIDE sealing faces. Stainless

steel metal parts, BUNA-N elastomers.
• Upper: CARBON VS. CERAMIC sealing faces. Stainless steel metal parts, BUNA-N elastomers.
Seal Sensor Probe: Located in oil-filled chamber. If pumpage should begin to leak past lower seal it indicates to pump control panel a fault has occurred. Requires optional Seal Fail Circuit in the control panel.
Shaft: Corrosion resistant, stainless steel. Threaded design. Locknut on all models to guard against component damage on accidental reverse rotation.
Fasteners: 300 series stainless steel.
Capable of running dry without damage to components.
Designed for continuous operation when fully submerged.

Estimated delivery is 3 weeks

Specs & Curve

Goulds Technical Brochure

ADDITIONAL INFORMATION

Weight	90 lbs
Dimensions	26 × 20 × 16 in
Best Efficiency Point	30 GPM @ 40 FTH
Connections	2" NPT
Phase	3
Solid Size	.75
Voltage	575
Wetted Material	CAST IRON-BUNA

PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350