

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS BOOSTER PUMP, 304SS W/NBR SEAL, 3 PHASE 440-480V, BM 18-4

90 GPM @ 63 PSI | IP66 | 5.5HP | Victaulic Connection 3.50" | 6" Pump | Straight Pipe Connections | Check lead time before ordering

Direct Replacement for BM 17

The motor power ranges from 1HP to 124HP. The motor must be controlled by a VFD and protected by Pt100 sensors. The VFD is sold as a separate. We recommend a Grundfos CUE VFD; however, VFDs from alternative suppliers can be used as well.



SKU: 93078096

Stock: Out of stock contact us for

lead time

Categories: Grundfos BM Booster

<u>Pumps</u>

Model Number BM 18-4



Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

Part Number 93078096

GALLERY IMAGES




Fig. 1 Positional requirements



www.pfcestore.com - 763-425-7890 / 800-328-2350

PRODUCT DESCRIPTION

Grundfos BM Pumps and BMhp booster modules are designed for pressure boosting, liquid transfer and circulation in systems with a high static pressure.

The pumps are suitable for pumping thin, non-explosive liquids, not containing abrasive particles or fibres. The liquid must not attack the pump materials chemically and mechanically.

The sound pressure level of BM 4" and BM and BMhp 6" booster modules is lower than 70 dB(A).

The sound pressure level of BM and BMhp 8" booster modules is lower than 80 dB(A).

Specs & Curve

Install Manual

ADDITIONAL INFORMATION

Weight 212 lbs

Dimensions $67 \times 12 \times 12$ in

Best Efficiency Point 90 GPM @ 140 FTH

Wetted Material <u>304SS-NBR</u>