

www.pfcestore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS CM 1-3 PUMP, 304SS, EPDM SEAL, THREE PHASE

BEP 9 GPM @ 80 FTH | Connections 1" NPT | Horse Power .58 | Three Phase | Volts 230-460 | Wetted Material-304SS-EPDM



SKU: 97568252 Stock: Out of stock contact us for lead time Categories: <u>Grundfos CM Pumps</u>

Model Number 97568252 Part Number CM 1-3 A-S-I-E-AQQV E-A-A-N

# **PRODUCT DESCRIPTION**

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM pumps are fitted with mains-operated motors, whereas the motors for CME



#### www.pfcestore.com - 763-425-7890 / 800-328-2350

pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

• AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids • AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

### Estimated delivery is 3 to 4 weeks

Curves & Specs

<u>Manual</u>

# **ADDITIONAL INFORMATION**

Weight	32 lbs
Dimensions	$26 \times 20 \times 20$ in
Best Efficiency Point	<u>9 GPM @ 80 FTH</u>
Horse Power	<u>0.58</u>
Phase	<u>3</u>
Voltage	<u>208-230-460</u>
Wetted Material	<u>304SS-EPDM</u>