

www.pfcstore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS CM 1-4 PUMP, 316SS, VITON SEAL, THREE PHASE

BEP 9 GPM @ 110 FTH |  
Connections 1" NPT | Horse Power  
1 | Three Phase | Volts 230-460 |  
Wetted Material-316SS-Viton



---

**SKU:** 97568247

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos CM Pumps](#)

**Model Number** 97568247

**Part Number** CM 1-4 A-S-G-V-  
AQQV E-A-A-N

## PRODUCT DESCRIPTION

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM pumps are fitted with mains-operated motors, whereas the motors for CME

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

- AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
- AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

**Estimated delivery is 3 to 4 weeks**

[Curves & Specs](#)

[Manual](#)

## ADDITIONAL INFORMATION

|                              |                        |
|------------------------------|------------------------|
| <b>Weight</b>                | 34 lbs                 |
| <b>Dimensions</b>            | 26 × 20 × 20 in        |
| <b>Best Efficiency Point</b> | <u>9 GPM @ 110 FTH</u> |
| <b>Horse Power</b>           | <u>1</u>               |
| <b>Phase</b>                 | <u>3</u>               |
| <b>Voltage</b>               | <u>208-230-460</u>     |
| <b>Wetted Material</b>       | <u>316SS-VITON</u>     |

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

BEP 9 GPM @ 110 FTH | Connections 1" NPT | Horse Power 1 | Three Phase |  
Volts 230-460 | Wetted Material-316SS-Viton