

www.pfcestore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS CM 10-1 PUMP CAST IRON, 304SS, EPDM SEAL, 3 PHASE

BEP 60 GPM @ 55 FTH |  
Connections 1.5" x 1.5" NPT |  
Horse Power 1.5 | 3 Phase | Volts  
208-230-460 | Wetted Material  
Cast Iron-304SS-EPDM



---

**SKU:** 99087480

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos CM Pumps](#)

**Model Number** 99087480

**Part Number** CM 10-1 A-S-A-E-  
AQQE E-A-A-N

## PRODUCT DESCRIPTION

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

pumps are fitted with mains-operated motors, whereas the motors for CME pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

- AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
- AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

**Estimated delivery is 3 to 4 weeks**

[Curves & Specs](#)

[Manual](#)

## ADDITIONAL INFORMATION

|                              |                                      |
|------------------------------|--------------------------------------|
| <b>Weight</b>                | 65 lbs                               |
| <b>Dimensions</b>            | 26 × 20 × 20 in                      |
| <b>Best Efficiency Point</b> | <a href="#">60 GPM @ 55 FTH</a>      |
| <b>Horse Power</b>           | <a href="#">1.5</a>                  |
| <b>Phase</b>                 | <a href="#">3</a>                    |
| <b>Voltage</b>               | <a href="#">208-230-460</a>          |
| <b>Wetted Material</b>       | <a href="#">CAST IRON-304SS-EPDM</a> |

**www.pfcestore.com - 763-425-7890 / 800-328-2350**