

www.pfcestore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS CM 10-2 PUMP, 316SS, VITON SEAL, THREE PHASE

BEP 45 GPM @125 FTH |  
Connections 1.5" X 1.5" NPT |  
Horse Power 4| Three Phase | Volts  
230-460 | Wetted Material-316SS-  
Viton



**SKU:** 96806991

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos CM Pumps](#)

**Model Number** 96806991

**Part Number** CM 10-2 A-S-G-V-  
AQQV E-A-A-N

## PRODUCT DESCRIPTION

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM

www.pfcestore.com - 763-425-7890 / 800-328-2350

pumps are fitted with mains-operated motors, whereas the motors for CME pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

- AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
- AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

**Estimated delivery is 3 to 4 weeks**

[Curves & Specs](#)  
[Manual](#)

ADDITIONAL INFORMATION

Weight	65 lbs
Dimensions	26 × 20 × 20 in
Best Efficiency Point	<a href="#">45 GPM @ 125 FTH</a>
Horse Power	<a href="#">4</a>
Phase	<a href="#">3</a>
Voltage	<a href="#">208-230-460</a>
Wetted Material	<a href="#">316SS-VITON</a>

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350