PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

GRUNDFOS CM 10-2 PUMP CAST IRON, 304SS, EPDM SEAL, 3 PHASE

BEP 60 GPM @ 115 FTH | Connections 1.5" x 1.5" NPT | Horse Power 3 | 3 Phase | Volts 208-230-460 | Wetted Material Cast Iron-304SS-EPDM

SKU: 97568516
Stock: Out of stock contact us for lead time
Categories: Grundfos CM Pumps

Model Number 97568516
Part Number CM 10-2 A-S-A-E-AQQE E-A-A-N

PRODUCT DESCRIPTION

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM

pumps are fitted with mains-operated motors, whereas the motors for CME pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

• AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
• AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

Estimated delivery is 3 to 4 weeks

Curves & Specs

Manual

ADDITIONAL INFORMATION

Weight	80 lbs
Dimensions	26 × 20 × 20 in
Best Efficiency Point	60 GPM @ 115 FTH
Horse Power	3
Phase	3
Voltage	208-230-460
Wetted Material	CAST IRON-304SS-EPDM

PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350