

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS CM 10-2 PUMP CAST IRON, 304SS, VITON SEAL, 3 PHASE

BEP 60 GPM @ 115 FTH |
Connections 1.5" x 1.5" NPT |
Horse Power 3 | 3 Phase | Volts
208-230-460 | Wetted Material
Cast Iron-304SS-Viton



SKU: 97568518

Stock: Out of stock contact us for

lead time

Categories: Grundfos CM Pumps

Model Number 97568518

Part Number CM 10-2 A-S-A-VAQQV E-A-A-N

PRODUCT DESCRIPTION

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM



www.pfcestore.com - 763-425-7890 / 800-328-2350

pumps are fitted with mains-operated motors, whereas the motors for CME pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

Estimated delivery is 3 to 4 weeks

Curves & Specs

<u>Manual</u>

ADDITIONAL INFORMATION

Weight 80 lbs

Dimensions $26 \times 20 \times 20$ in

Best Efficiency Point 60 GPM @ 115 FTH

Horse Power <u>3</u>

<u>3</u>

Voltage <u>208-230-460</u>

Wetted Material <u>CAST IRON-304SS-VITON</u>



www.pfcestore.com - 763-425-7890 / 800-328-2350