

www.pfcestore.com - 763-425-7890 / 800-328-2350



**GRUNDFOS CM 10-3  
PUMP, 316SS, EPDM SEAL,  
THREE PHASE**

BEP 45 GPM @208 FTH |  
Connections 1.5" X 1.5" NPT |  
Horse Power 5.5| Three Phase |  
Volts 230-460 | Wetted  
Material-316SS-EPDM



---

**SKU:** 97568507

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos CM Pumps](#)

**Model Number** 97568507

**Part Number** CM 10-3 A-S-G-E-  
AQQE E-A-A-N

## PRODUCT DESCRIPTION

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM

www.pfcestore.com - 763-425-7890 / 800-328-2350

pumps are fitted with mains-operated motors, whereas the motors for CME pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

- AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
- AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

**Estimated delivery is 3 to 4 weeks**

[Curves & Specs](#)  
[Manual](#)

ADDITIONAL INFORMATION

Weight	84 lbs
Dimensions	26 × 20 × 20 in
Best Efficiency Point	<a href="#">45 GPM @ 208 FTH</a>
Horse Power	<a href="#">5.5</a>
Phase	<a href="#">3</a>
Voltage	<a href="#">208-230-460</a>
Wetted Material	<a href="#">316SS-EPDM</a>

**www.pfcestore.com - 763-425-7890 / 800-328-2350**