

www.pfcstore.com - 763-425-7890 / 800-328-2350



## **GRUNDFOS CM 15-2 PUMP, 316SS, VITON SEAL, THREE PHASE**

BEP 70 GPM @150 FTH |  
Connections 2" X 2" NPT | Horse  
Power 5.5 | Three Phase | Volts  
230-460 | Wetted Material-316SS-  
Viton



---

**SKU:** 96943321

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos CM Pumps](#)

**Model Number** 96943321

**Part Number** CM 15-2 A-S-G-V-  
AQQV E-A-A-N

## **PRODUCT DESCRIPTION**

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM

www.pfcestore.com - 763-425-7890 / 800-328-2350

pumps are fitted with mains-operated motors, whereas the motors for CME pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

- AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
- AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

**Estimated delivery is 3 to 4 weeks**

[Curves & Specs](#)  
[Manual](#)

ADDITIONAL INFORMATION

Weight	83 lbs
Dimensions	26 × 20 × 20 in
Best Efficiency Point	<a href="#">70 GPM @ 150 FTH</a>
Horse Power	<a href="#">5.5</a>
Phase	<a href="#">3</a>
Voltage	<a href="#">208-230-460</a>
Wetted Material	<a href="#">316SS-VITON</a>

**www.pfcestore.com - 763-425-7890 / 800-328-2350**