

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS CM 15-3 PUMP, 316SS, EPDM SEAL, THREE PHASE

BEP 70 GPM @230 FTH |
Connections 2" X 2" NPT | Horse
Power 10 | Three Phase | Volts
230-460 | Wetted Material-316SS-
EPDM



SKU: 99322449

Stock: Out of stock contact us for
lead time

Categories: [Grundfos CM Pumps](#)

Model Number 99322449

Part Number CM 15-3 A-S-G-E-
AQQE E-A-A-N

PRODUCT DESCRIPTION

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM

www.pfcstore.com - 763-425-7890 / 800-328-2350

pumps are fitted with mains-operated motors, whereas the motors for CME pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

- AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
- AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

Estimated delivery is 3 to 4 weeks

[Curves & Specs](#)

[Manual](#)

ADDITIONAL INFORMATION

Weight	101 lbs
Dimensions	26 × 20 × 20 in
Best Efficiency Point	<u>70 GPM @ 230 FTH</u>
Horse Power	<u>10</u>
Phase	<u>3</u>
Voltage	<u>208-230-460</u>
Wetted Material	<u>316SS-EPDM</u>

www.pfcestore.com - 763-425-7890 / 800-328-2350