

www.pfcestore.com - 763-425-7890 / 800-328-2350



# GRUNDFOS CM 15-3 PUMP CAST IRON, 304SS, EPDM SEAL, 3 PHASE

BEP 90 GPM @ 220 FTH | Connections 2" x 2" NPT | Horse Power 7.5 | 3 Phase | Volts 208-230-460 | Wetted Material Cast Iron-304SS-EPDM



SKU: 99059746 Stock: Out of stock contact us for lead time Categories: <u>Grundfos CM Pumps</u>

Model Number 99059746 Part Number CM 15-3 A-S-A-E-AQQE E-A-A-N

# **PRODUCT DESCRIPTION**

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM



#### www.pfcestore.com - 763-425-7890 / 800-328-2350

pumps are fitted with mains-operated motors, whereas the motors for CME pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

### Estimated delivery is 3 to 4 weeks

Curves & Specs

<u>Manual</u>

## **ADDITIONAL INFORMATION**

Weight	112 lbs
Dimensions	26 × 20 × 20 in
<b>Best Efficiency Point</b>	<u>90 GPM @ 220 FTH</u>
Horse Power	<u>7.5</u>
Phase	<u>3</u>
Voltage	208-230-460
Wetted Material	CAST IRON-304SS-EPDM



www.pfcestore.com - 763-425-7890 / 800-328-2350