

www.pfcestore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS CM 25-1 PUMP CAST IRON, 304SS, VITON SEAL, 3 PHASE

BEP 120 GPM @ 80 FTH |  
Connections 2" x 2" NPT | Horse  
Power 5.4 | 3 Phase | Volts  
208-230-460 | Wetted Material  
Cast Iron-304SS-Viton



---

**SKU:** 97568600

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos CM Pumps](#)

**Model Number** 97568600

**Part Number** CM 25-1 A-S-A-V-  
AQQV E-A-A-N

## PRODUCT DESCRIPTION

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM

www.pfcestore.com - 763-425-7890 / 800-328-2350

pumps are fitted with mains-operated motors, whereas the motors for CME pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

- AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
- AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

**Estimated delivery is 3 to 4 weeks**

[Curves & Specs](#)  
[Manual](#)

ADDITIONAL INFORMATION

|                       |                                       |
|-----------------------|---------------------------------------|
| Weight                | 92 lbs                                |
| Dimensions            | 26 × 20 × 20 in                       |
| Best Efficiency Point | <a href="#">120 GPM @ 80 FTH</a>      |
| Horse Power           | <a href="#">5</a>                     |
| Phase                 | <a href="#">3</a>                     |
| Voltage               | <a href="#">208-230-460</a>           |
| Wetted Material       | <a href="#">CAST IRON-304SS-VITON</a> |

**[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350**