

www.pfcestore.com - 763-425-7890 / 800-328-2350



## **GRUNDFOS CM 25-2 PUMP, 304SS, VITON SEAL, THREE PHASE**

BEP 100 GPM @ 150 FTH |  
Connections 2" X 2" NPT | Horse  
Power 10 | Three Phase | Volts  
230-460 | Wetted Material-304SS-  
Viton



---

**SKU:** 99327144

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos CM Pumps](#)

**Model Number** 99327144

**Part Number** CM 25-2 A-S-I-V-  
AQQV E-A-A-N

## **PRODUCT DESCRIPTION**

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

pumps are fitted with mains-operated motors, whereas the motors for CME pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

- AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
- AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

**Estimated delivery is 3 to 4 weeks**

Curves & Specs

[Manual](#)

## ADDITIONAL INFORMATION

|                              |                                   |
|------------------------------|-----------------------------------|
| <b>Weight</b>                | 101 lbs                           |
| <b>Dimensions</b>            | 26 × 20 × 20 in                   |
| <b>Best Efficiency Point</b> | <a href="#">100 GPM @ 150 FTH</a> |
| <b>Horse Power</b>           | <a href="#">10</a>                |
| <b>Phase</b>                 | <a href="#">3</a>                 |
| <b>Voltage</b>               | <a href="#">208-230-460</a>       |
| <b>Wetted Material</b>       | <a href="#">304SS-VITON</a>       |

**[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350**