

www.pfcestore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS CM 3-2 PUMP, 316SS, VITON SEAL, SINGLE PHASE

BEP 14 GPM @65 FTH | Connections 1" NPT | Horse Power 1 | Single Phase | Volts 115-230 | Wetted Material-316SS-Viton



SKU: 97568302 Stock: Out of stock contact us for lead time Categories: <u>Grundfos CM Pumps</u>

Model Number 97568302 Part Number CM 3-2 A-S-G-V-AQQV B-A-A-N

# **PRODUCT DESCRIPTION**

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM pumps are fitted with mains-operated motors, whereas the motors for CME



#### www.pfcestore.com - 763-425-7890 / 800-328-2350

pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

• AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids • AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

### Estimated delivery is 3 to 4 weeks

Curves & Specs

<u>Manual</u>

# **ADDITIONAL INFORMATION**

| Weight                | 33 lbs                 |
|-----------------------|------------------------|
| Dimensions            | 26 × 20 × 20 in        |
| Best Efficiency Point | <u>14 GPM @ 65 FTH</u> |
| Horse Power           | .805                   |
| Phase                 | <u>1</u>               |
| Voltage               | <u>115-230</u>         |
| Wetted Material       | <u>316SS-VITON</u>     |