

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS CM 3-3 PUMP, 304SS, EPDM SEAL, THREE PHASE

BEP 14 GPM @ 100 FTH |
Connections 1" NPT | Horse Power
1.0 | Three Phase | Volts 230-460 |
Wetted Material-304SS-EPDM



SKU: 97568353

Stock: Out of stock contact us for
lead time

Categories: [Grundfos CM Pumps](#)

Model Number 97568353

Part Number CM 3-3 A-S-I-E-
AQQE E-A-A-N

PRODUCT DESCRIPTION

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM pumps are fitted with mains-operated motors, whereas the motors for CME

www.pfcstore.com - 763-425-7890 / 800-328-2350

pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

- AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
- AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

Estimated delivery is 3 to 4 weeks

[Curves & Specs](#)

[Manual](#)

ADDITIONAL INFORMATION

| | |
|------------------------------|---|
| Weight | 33 lbs |
| Dimensions | 26 × 20 × 20 in |
| Best Efficiency Point | <u>14 GPM @ 100 FTH</u> |
| Horse Power | <u>1</u> |
| Phase | <u>3</u> |
| Voltage | <u>208-230-460</u> |
| Wetted Material | <u>304SS-EPDM</u> |