

www.pfcstore.com - 763-425-7890 / 800-328-2350



**GRUNDFOS CM 3-6 PUMP,
304SS, EPDM SEAL,
SINGLE PHASE**

BEP 14 GPM @ 200 FTH |
Connections 1" NPT | Horse Power
2 | Single Phase | Volts 115-230 |
Wetted Material-304SS-EPDM



SKU: 98125819

Stock: Out of stock contact us for
lead time

Categories: [Grundfos CM Pumps](#)

Model Number 98125819

Part Number CM 3-6 A-S-I-E-
AQQE B-A-A-N

PRODUCT DESCRIPTION

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM pumps are fitted with mains-operated motors, whereas the motors for CME

www.pfcstore.com - 763-425-7890 / 800-328-2350

pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

- AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
- AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

Estimated delivery is 3 to 4 weeks

[Curves & Specs](#)

[Manual](#)

ADDITIONAL INFORMATION

Weight	58 lbs
Dimensions	26 × 20 × 20 in
Best Efficiency Point	14 GPM @ 200 FTH
Horse Power	2
Phase	1
Voltage	115-230
Wetted Material	304SS-EPDM

www.pfcestore.com - 763-425-7890 / 800-328-2350

BEP 14 GPM @ 200 FTH | Connections 1" NPT | Horse Power 2 | Single Phase |
Volts 115-230 | Wetted Material-304SS-EPDM