

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS CM 3-8 PUMP, 316SS, VITON SEAL, THREE PHASE

BEP 14 GPM @300 FTH | Connections 1" NPT | Horse Power 4 | Three Phase | Volts 230-440 | Wetted Material-316SS-Viton



SKU: 97568350 Stock: Out of stock contact us for lead time Categories: <u>Grundfos CM Pumps</u>

Model Number 97568350 Part Number CM 3-8 A-S-G-V-AQQV E-A-A-N

PRODUCT DESCRIPTION

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM pumps are fitted with mains-operated motors, whereas the motors for CME



www.pfcestore.com - 763-425-7890 / 800-328-2350

pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

• AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids • AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

Estimated delivery is 3 to 4 weeks

Curves & Specs

<u>Manual</u>

ADDITIONAL INFORMATION

| Weight | 60 lbs |
|------------------------------|-----------------------------|
| Dimensions | $26 \times 20 \times 20$ in |
| Best Efficiency Point | <u>14 GPM @ 300 FTH</u> |
| Horse Power | <u>4</u> |
| Phase | <u>3</u> |
| Voltage | 208-230-460 |
| Wetted Material | <u>316SS-VITON</u> |