PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

GRUNDFOS CM 5-3 PUMP, 304SS, VITON SEAL, THREE PHASE

BEP 25 GPM @ 101 FTH | Connections 1" X 1.25" NPT | Horse Power 1.5 | Three Phase | Volts 230-460 | Wetted Material-304SS-Viton

SKU: 99155398
Stock: Out of stock contact us for lead time
Categories: Grundfos CM Pumps

Model Number 99155398
Part Number CM 5-3 A-S-I-V-AQQV E-A-A-N

PRODUCT DESCRIPTION

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM

pumps are fitted with mains-operated motors, whereas the motors for CME pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

• AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
• AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

Estimated delivery is 3 to 4 weeks

Curves & Specs

Manual

ADDITIONAL INFORMATION

Weight	36 lbs
Dimensions	26 × 20 × 20 in
Best Efficiency Point	25 GPM @ 101 FTH
Horse Power	1.5
Phase	3
Voltage	230-460
Wetted Material	304SS-VITON

PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350