

www.pfcestore.com - 763-425-7890 / 800-328-2350



**GRUNDFOS CM 5-3 PUMP,
316SS, VITON SEAL,
SINGLE PHASE**

BEP 25 GPM @101 FTH |
Connections 1.25" X 1" NPT | Horse
Power 1.5 | Single Phase | Volts
115-230 | Wetted Material-316SS-
Viton



SKU: 97568403

Stock: Out of stock contact us for
lead time

Categories: [Grundfos CM Pumps](#)

Model Number 97568403

Part Number CM 5-3 A-S-G-V-
AQQV B-A-A-N

PRODUCT DESCRIPTION

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM

www.pfcstore.com - 763-425-7890 / 800-328-2350

pumps are fitted with mains-operated motors, whereas the motors for CME pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

- AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
- AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

Estimated delivery is 3 to 4 weeks

[Curves & Specs](#)

[Manual](#)

ADDITIONAL INFORMATION

Weight	39 lbs
Dimensions	26 × 20 × 20 in
Best Efficiency Point	<u>25 GPM @ 101 FTH</u>
Horse Power	<u>1.5</u>
Phase	<u>1</u>
Voltage	<u>115-230</u>
Wetted Material	<u>316SS-VITON</u>

www.pfcestore.com - 763-425-7890 / 800-328-2350