

www.pfcstore.com - 763-425-7890 / 800-328-2350



GRUNDFOS CM 5-4 PUMP, 316SS, VITON SEAL, THREE PHASE

BEP 25 GPM @153 FTH |
Connections 1.25" X 1" NPT | Horse
Power 3 | Three Phase | Volts
230-460 | Wetted Material-316SS-
Viton



SKU: 97568437

Stock: Out of stock contact us for
lead time

Categories: [Grundfos CM Pumps](#)

Model Number 97568437

Part Number CM 5-4 A-S-G-V-
AQQV E-A-A-N

PRODUCT DESCRIPTION

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM

www.pfcstore.com - 763-425-7890 / 800-328-2350

pumps are fitted with mains-operated motors, whereas the motors for CME pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

- AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
- AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

Estimated delivery is 3 to 4 weeks

[Curves & Specs](#)

[Manual](#)

ADDITIONAL INFORMATION

Weight	57 lbs
Dimensions	26 × 20 × 20 in
Best Efficiency Point	25 GPM @ 153 FTH
Horse Power	3
Phase	3
Voltage	208-230-460
Wetted Material	316SS-VITON

www.pfcestore.com - 763-425-7890 / 800-328-2350

BEP 25 GPM @153 FTH | Connections 1.25" X 1" NPT | Horse Power 3| Three Phase | Volts 230-460 | Wetted Material-316SS-Viton