


www.pfcstore.com - 763-425-7890 / 800-328-2350



**GRUNDFOS CM 5-5 PUMP,  
304SS, EPDM SEAL,  
SINGLE PHASE**

BEP 25 GPM @ 165FTH |  
Connections 1" X 1.25" NPT |  
Horse Power 3 | Single Phase |  
Volts 115-230 | Wetted  
Material-304SS-EPDM



---

**SKU:** 98125911

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos CM Pumps](#)

**Model Number** 98125911

**Part Number** CM 5-5 A-S-I-E-  
AQQE B-A-A-N

## PRODUCT DESCRIPTION

Grundfos CM pump has been created with compactness, flexibility and reliability as its central features. This horizontal multistage close-coupled pump is a compact, reliable and quiet pump designed to work in a variety of applications.

The difference between the CM and the CME pump ranges is the motor. CM

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

pumps are fitted with mains-operated motors, whereas the motors for CME pumps have an integrated frequency converter and PID controller.

A Grundfos engineered mechanical shaft seal has been designed to eliminate industry-wide problems with shaft seals sticking where SIC-SIC seal faces are used. The solution builds on both the implementation of a rotation stop on the stationary ring and different surface finishing on both the stationary and rotating rings.

The CM and CME pumps are available in cast iron or stainless steel

- AISI 304/DIN 1.4301 stainless steel for water and non-corrosive liquids
- AISI 316/DIN 1.4401 stainless steel offers

Product photo could vary from the actual product

**Estimated delivery is 3 to 4 weeks**

[Curves & Specs](#)

[Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	57 lbs
<b>Dimensions</b>	26 × 20 × 20 in
<b>Best Efficiency Point</b>	<a href="#">25 GPM @ 165 FTH</a>
<b>Horse Power</b>	<a href="#">3</a>
<b>Phase</b>	<a href="#">1</a>
<b>Voltage</b>	<a href="#">115-230</a>
<b>Wetted Material</b>	<a href="#">304SS-EPDM</a>

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

BEP 25 GPM @ 165FTH | Connections 1" X 1.25" NPT | Horse Power 3 | Single Phase | Volts 115-230 | Wetted Material-304SS-EPDM