

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS CR 3-23 VERTICAL CENTRIFUGAL PUMP 3 PHASE WITH EPDM

96083232 Wetted Parts: Cast Iron,
304SS, EPDM Seal | 3 Phase | 5 hp
| 3600 rpm | 1.25" ANSI Flanged
250lb | BEP 14 GPM @ 590 FTH



SKU: 99916355

Stock: Out of stock contact us for
lead time

Categories: [Grundfos CR Pumps](#)

Model Number CR3-23 A-FGJ-A-E-
HQQE

Part Number 99916355

PRODUCT DESCRIPTION

CR 3 pumps Vertical, multistage centrifugal pump with suction and discharge ports on the same level. The pump head and base are in cast iron. All other wetted parts are in stainless steel (EN 1.4301)(AISI 304)

www.pfcstore.com - 763-425-7890 / 800-328-2350

Estimated delivery is 2 to 4 weeks

Grundfos pump is fitted with a balanced O-ring seal unit with a rigid torque-transmission system. This seal type is assembled in a cartridge unit which makes replacement safe and easy. Due to the balancing, this seal type is suitable for high-pressure applications. The cartridge construction also protects the pump shaft from possible wear from a dynamic O-ring between pump shaft and shaft seal.

Primary seal:

- Rotating seal ring material: silicon carbide (SiC)
- Stationary seat material: silicon carbide (SiC)

This material pairing is used where higher corrosion resistance is required. The high hardness of this material pairing offers good resistance against abrasive particles. Secondary seal material: EPDM (ethylene-propylene rubber) EPDM has excellent resistance to hot water. EPDM is not suitable for mineral oils.

The shaft seal is screwed into the pump head. The chambers and impellers are made of stainless-steel sheet. The chambers are provided with a PTFE neck ring offering improved sealing and high efficiency. The impellers have smooth surfaces, and the shape of the blades ensure a high efficiency.

The base is made of cast iron. The flanges and base are cast in one piece. The outlet side of the base has a combined drain plug and bypass valve. The pump is secured to the foundation by four bolts through the base plate.

The motor is a totally enclosed, fan-cooled motor with principal dimensions to IEC and DIN standards.

The motor is flange-mounted with tapped-hole flange (FT). Motor-mounting designation in accordance with IEC 60034-7: IM B 14 (Code I) / IM 3601 (Code II). Electrical tolerances comply with IEC 60034.

[Specs & Curve](#)

[CR DATA BOOK](#)

www.pfcstore.com - 763-425-7890 / 800-328-2350

ADDITIONAL INFORMATION

Weight	135 lbs
Dimensions	42 × 16 × 16 in
Best Efficiency Point	<u>14 GPM @ 590 FTH</u>
Connections	<u>1.25" Flange</u>
Hertz	<u>60</u>
Horse Power	<u>5</u>
Motor Type	<u>TEFC</u>
Phase	<u>3</u>
RPM	<u>3600</u>
Voltage	<u>208-230-460</u>
Wetted Material	<u>CAST IRON-304SS-EPDM</u>