

www.pfcstore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS CRE 20-2, CAST IRON/304SS & EPDM WITH VFD, PRESSURE SENSOR & FLANGES

Wetted Material CI/304SS-EPDM |  
Input Volts 440-480 | 2" Ansi  
Flanges | BEP 90 GPM @ 111 FTH



---

**SKU:** 99076271

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos VFD CRE  
Pumps](#)

**Tags:** [GRUNDFOS CRNE5 PUMPS](#)

**Model Number** 99076271

**Part Number** CRE 20-2 N-GJ-A-E-  
HQQE

## PRODUCT DESCRIPTION

**Typical delivery is 3 to 4 weeks**

The CRE 20 terminal box has a number of inputs and outputs enabling the motor to be used in advanced applications where many inputs and outputs are required:

- two dedicated digital inputs

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

- three analog inputs, 0(4)-20 mA, 0-5 V, 0-10 V, 0.5 - 3.5 V; the factory-fitted pressure sensor is connected to one of these inputs
  - 5 V voltage supply to potentiometer and sensor
    - one analog output, 0-10 V, 0(4)-20 mA
- two configurable digital inputs or open-collector outputs
  - two Pt100/Pt1000 inputs
  - LiqTec, dry-running protection sensor input
  - Grundfos Digital Sensor input and output
    - 24 V voltage supply for sensors
- two signal-relay outputs (potential-free contacts)
  - GENibus connection
- interface for Grundfos CIM fieldbus module.

#### Further product details

The pump is equipped with a pressure sensor registering pump outlet pressure and enabling controlled pump operation based on constant pressure.

The operating panel on the motor terminal box features a four-inch TFT display, push-buttons and the Grundfos Eye indicator.

The display gives an intuitive and user-friendly interface to all functions.

#### [Curves & Specs](#)

#### [Databook](#)

#### [Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	170 lbs
<b>Dimensions</b>	38 × 18 × 18 in
<b>Best Efficiency Point</b>	<a href="#"><u>90 GPM @ 110 FTH</u></a>

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

<b>Connections</b>	<u>2" ANSI FLANGE</u>
<b>Horse Power</b>	<u>5</u>
<b>Input Volts</b>	<u>440-480</u>
<b>Phase</b>	<u>3</u>
<b>Wetted Material</b>	<u>CAST IRON-304SS-EPDM</u>