

www.pfcstore.com - 763-425-7890 / 800-328-2350



**GRUNDFOS CRN 10-16
VERTICAL CENTRIFUGAL
PUMP 316SS, 3 PHASE
WITH VITON**

96522818 Wetted Parts: 316SS,
Viton Seal | 3 Phase | 15 hp | 3600
rpm | 2" Flange 300lb | BEP 45
GPM @ 670 FTH



SKU: 99917433

Stock: Out of stock contact us for
lead time

Categories: [Grundfos CRN Pumps](#)

Model Number CRN10-16 A-FGJ-
A-V-HQQV

Part Number 99917433

PRODUCT DESCRIPTION

[fusion_builder_container hundred_percent="no"
hundred_percent_height="no" hundred_percent_height_scroll="no"
hundred_percent_height_center_content="yes" equal_height_columns="no"
menu_anchor="" hide_on_mobile="small-visibility,medium-visibility,large-
visibility" class="" id="" background_color="" background_image=""]

www.pfcstore.com - 763-425-7890 / 800-328-2350

```
background_position="center center" background_repeat="no-repeat"
fade="no" background_parallax="none" enable_mobile="no"
parallax_speed="0.3" video_mp4="" video_webm="" video_ogv=""
video_url="" video_aspect_ratio="16:9" video_loop="yes"
video_mute="yes" video_preview_image="" border_size=""
border_color="" border_style="solid" margin_top="" margin_bottom=""
padding_top="" padding_right="" padding_bottom=""
padding_left=""[fusion_builder_row][fusion_builder_column type="1_2"
layout="1_2" spacing="" center_content="no" link="" target="_self"
min_height="" hide_on_mobile="small-visibility,medium-visibility,large-
visibility" class="" id="" background_color="" background_image=""
background_position="left top" background_repeat="no-repeat"
hover_type="none" border_size="0" border_color="" border_style="solid"
border_position="all" padding_top="" padding_right="" padding_bottom=""
padding_left="" margin_top="" margin_bottom="" animation_type=""
animation_direction="left" animation_speed="0.3" animation_offset=""
last="no"][fusion_text columns="" column_min_width=""
column_spacing="" rule_style="default" rule_size="" rule_color=""
hide_on_mobile="small-visibility,medium-visibility,large-visibility" class=""
id="" animation_type="" animation_direction="left"
animation_speed="0.3" animation_offset=""]]
```

Grundfos CRN 10 Vertical, multistage centrifugal pump with inlet and outlet ports on same the level (inline). Pump materials in contact with the liquid are in high-grade stainless steel. A cartridge shaft seal ensures high reliability, safe handling, and easy access and service. Power transmission is via a rigid split coupling.

Pipe connection is via combined DIN-ANSI-JIS flanges. The pump is fitted with a 1-phase, fan-cooled asynchronous motor.

Estimated delivery is 2 to 4 weeks

Contact us for actual delivery

Product photo could vary from the actual product

www.pfcestore.com - 763-425-7890 / 800-328-2350

```
[/fusion_text][/fusion_builder_column][fusion_builder_column type="1_2"
  layout="1_2" spacing="" center_content="no" link="" target="_self"
  min_height="" hide_on_mobile="small-visibility,medium-visibility,large-
  visibility" class="" id="" background_color="" background_image=""
  background_position="left top" background_repeat="no-repeat"
  hover_type="none" border_size="0" border_color="" border_style="solid"
border_position="all" padding_top="" padding_right="" padding_bottom=""
  padding_left="" margin_top="" margin_bottom="" animation_type=""
  animation_direction="left" animation_speed="0.3" animation_offset=""
  last="no"][fusion_button
link="https://pfcestore.com/wp-content/uploads/2020/05/96522818_CRN_1
016_AFGJAVHQV.pdf" text_transform="" title="" target="_blank"
  link_attributes="" alignment="" modal="" hide_on_mobile="small-
  visibility,medium-visibility,large-visibility" class="" id="" color="default"
  button_gradient_top_color="" button_gradient_bottom_color=""
  button_gradient_top_color_hover=""
  button_gradient_bottom_color_hover="" accent_color=""
  accent_hover_color="" type="" bevel_color="" border_width=""
  border_radius="" border_color="" border_hover_color="" size=""
  stretch="default" icon="" icon_position="left" icon_divider="no"
  animation_type="" animation_direction="left" animation_speed="0.3"
  animation_offset=""]Specs & Curve[/fusion_button][fusion_separator
style_type="none" hide_on_mobile="small-visibility,medium-visibility,large-
  visibility" class="" id="" sep_color="" top_margin="5px"
  bottom_margin="5px" border_size="" icon="" icon_circle=""
  icon_circle_color="" width="" alignment="center" /][fusion_button
link="https://pfcestore.com/wp-content/uploads/2020/11/WEG-MOTOR-CR-C
RI-CRN-DATABOOK.pdf" text_transform="" title="" target="_blank"
  link_attributes="" alignment="" modal="" hide_on_mobile="small-
  visibility,medium-visibility,large-visibility" class="" id="" color="default"
  button_gradient_top_color="" button_gradient_bottom_color=""
  button_gradient_top_color_hover=""
  button_gradient_bottom_color_hover="" accent_color=""
  accent_hover_color="" type="" bevel_color="" border_width="" size=""
  stretch="default" icon="" icon_position="left" icon_divider="no"
```

www.pfcestore.com - 763-425-7890 / 800-328-2350

animation_type="" animation_direction="left" animation_speed="0.3"
animation_offset="" border_radius=""]CRN DATA
BOOK[/fusion_button[/fusion_builder_column[/fusion_builder_row[/fusion_
builder_container]

ADDITIONAL INFORMATION

Weight	370 lbs
Dimensions	60 × 18 × 18 in
Best Efficiency Point	<u>45 GPM @ 670 FTH</u>
Connections	<u>2" ANSI FLANGE</u>
Hertz	<u>60</u>
Horse Power	<u>15</u>
Motor Type	<u>TEFC</u>
Phase	<u>3</u>
RPM	<u>3600</u>
Voltage	<u>208-230-460</u>
Wetted Material	<u>316SS-VITON</u>