

www.pfcstore.com - 763-425-7890 / 800-328-2350



GRUNDFOS LOW NPSH PUMP CR32-6-2

29Z53602 Wetted Parts: Cast Iron,
304SS, EPDM Seal | 3 Phase | 25
hp | 3600 rpm | 2.50 ANSI Flange|
BEP 120 GPM @ 450 FTH



SKU: 99968327

Stock: Out of stock contact us for
lead time

Categories: [Grundfos Low NPSH
Pumps](#)

Tags: [GRUNDFOS LOW NPSH
PUMPS](#)

Model Number CR 32-6-2 K-G-A-
E-HQQE

Part Number 99968327

GALLERY IMAGES

The technical drawing illustrates the SPS 6000 pump assembly from two perspectives: a front elevation and a side view.

Front View Dimensions:

- Total height: 19.50
- Top section width: 12.80
- Motor housing width: 11.30
- Distance between mounting feet: 11.00
- Flange connection: G 1/2
- Lower flange connection: 4 X G 1/2
- Bottom flange diameter: 6.69
- Internal vertical distance: 8.90
- Total base width: 12.60
- Mounting foot height: 4.13

Side View Dimensions:

- Overall width: 8 x 0.91
- Height from base to top of motor housing: 1.18
- Base plate thickness: 2.91
- Internal horizontal distance: 9.45
- Base plate width: 11.70
- Motor housing depth: 5.88
- Total depth: 7.50
- Base plate offset: 4 x 0.56

www.pfcstore.com - 763-425-7890 / 800-328-2350

PRODUCT DESCRIPTION

Grundfos Low NPSH Pump

Estimated delivery is 2 to 4 weeks

Contact us for actual delivery

Product photo could vary from the actual product

[Curve & Specs](#)

[Databook](#)

ADDITIONAL INFORMATION

Weight	550 lbs
Dimensions	65 × 18 × 18 in
Best Efficiency Point	<u>120 GPM @ 450 FTH</u>
Connections	<u>2.50" ANSI FLANGE</u>
Hertz	<u>60</u>
Horse Power	<u>25</u>
Motor Type	<u>TEFC</u>
Phase	<u>3</u>
RPM	<u>3600</u>
Voltage	<u>208-230-460</u>
Wetted Material	<u>CAST IRON-304SS-EPDM</u>

www.pfcestore.com - 763-425-7890 / 800-328-2350