

www.pfcestore.com - 763-425-7890 / 800-328-2350



GRUNDFOS MTR 1-22/22 COOLANT PUMP THREE PHASE-NEMA VERSION

Material: Cast Iron-304SS-Viton | Best Efficiency Point 9 GPM @ 510 FTH | Motor 3/60/208-230-460 Volt, 3 HP | Pump Depth 20.50" | Nema Version



SKU: 96515394 Stock: Out of stock contact us for lead time Categories: <u>Grundfos</u> <u>Coolant/Condensate Pumps</u>

Model Number MTR 1-22/22 A-WB-A-HUUV Part Number 96515394

PRODUCT DESCRIPTION

Grundfos MTR pumps are vertical multi and single stage centrifugal pumps designed for pumping of cooling lubricants for machine tools, condensate

PFC eStore Pumps, Filters & Controls store with B2B solution



www.pfcestore.com - 763-425-7890 / 800-328-2350

transfer and similar applications. All models are designed to be mounted on top of tanks with the pump stack immersed in the pumped liquid.

Heavy-duty, multistage pumps that offer a unique hydraulic design and an unequaled performance range. Cartridge shaft seal and a universal flange system enables rapid replacement and ensures reliability. Special priming screw in allows for liquid levels down to 1 inch (25 mm) and protects against dry running

Product photo could vary from the actual product

Estimated Delivery is 3 to 4 weeks

MTR Specs

MTR Manual

ADDITIONAL INFORMATION

Weight	90 lbs
Dimensions	50 × 18 × 18 in
Best Efficiency Point	<u>9 GPM @ 510 FTH</u>
Connections	<u>1.25" NPT</u>
Horse Power	<u>3</u>
Length	Pump Depth 20.50"
Phase	<u>3</u>
Voltage	208-230-460
Wetted Material	CAST IRON-304SS-VITON