

www.pfcstore.com - 763-425-7890 / 800-328-2350



GRUNDFOS MTR 1-23/23 COOLANT PUMP THREE PHASE-NEMA VERSION

Material: Cast Iron-304SS-Viton |
Best Efficiency Point 9 GPM @ 535
FTH | Motor 3/60/208-230-460 Volt,
3 HP | Pump Depth 21.20" | Nema
Version



SKU: 96515395

Stock: Out of stock contact us for
lead time

Categories: [Grundfos](#)
[Coolant/Condensate Pumps](#)

Model Number MTR 1-23/23 A-
WB-A-HUUV

Part Number 96515395

PRODUCT DESCRIPTION

Grundfos MTR pumps are vertical multi and single stage centrifugal pumps designed for pumping of cooling lubricants for machine tools, condensate

www.pfcstore.com - 763-425-7890 / 800-328-2350

transfer and similar applications. All models are designed to be mounted on top of tanks with the pump stack immersed in the pumped liquid.

Heavy-duty, multistage pumps that offer a unique hydraulic design and an unequaled performance range. Cartridge shaft seal and a universal flange system enables rapid replacement and ensures reliability. Special priming screw in allows for liquid levels down to 1 inch (25 mm) and protects against dry running

Product photo could vary from the actual product

Estimated Delivery is 3 to 4 weeks

[MTR Specs](#)

[MTR Manual](#)

ADDITIONAL INFORMATION

| | |
|------------------------------|---------------------------------------|
| Weight | 90 lbs |
| Dimensions | 50 × 18 × 18 in |
| Best Efficiency Point | 9 GPM @ 535 FTH |
| Connections | 1.25" NPT |
| Horse Power | 3 |
| Length | Pump Depth 21.20" |
| Phase | 3 |
| Voltage | 208-230-460 |
| Wetted Material | CAST IRON-304SS-VITON |

www.pfcstore.com - 763-425-7890 / 800-328-2350

Material: Cast Iron-304SS-Viton | Best Efficiency Point 9 GPM @ 535 FTH | Motor 3/60/208-230-460 Volt, 3 HP | Pump Depth 21.20" | Nema Version