



## GRUNDFOS MTR 1-3/3 COOLANT PUMP THREE PHASE-NEMA VERSION

Material: Cast Iron-304SS-Viton |  
Best Efficiency Point 9 GPM @ 67  
FTH | Motor 3/60/208-230-460 Volt,  
.50 HP | Pump Depth 7-1/16" |  
Nema Version



---

**SKU:** 96515379

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos](#)  
[Coolant/Condensate Pumps](#)

**Model Number** MTR 1-3/3 A-WB-  
A-HUUV

**Part Number** 96515379

## PRODUCT DESCRIPTION

Grundfos MTR pumps are vertical multi and single stage centrifugal pumps designed for pumping of cooling lubricants for machine tools, condensate

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

transfer and similar applications. All models are designed to be mounted on top of tanks with the pump stack immersed in the pumped liquid.

Heavy-duty, multistage pumps that offer a unique hydraulic design and an unequaled performance range. Cartridge shaft seal and a universal flange system enables rapid replacement and ensures reliability. Special priming screw in allows for liquid levels down to 1 inch (25 mm) and protects against dry running

Product photo could vary from the actual product

**Estimated Delivery is 3 to 4 weeks**

[MTR Specs](#)

[MTR Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	50 lbs
<b>Dimensions</b>	36 × 18 × 18 in
<b>Best Efficiency Point</b>	<a href="#">9 GPM @ 67 FTH</a>
<b>Connections</b>	<a href="#">1.25" NPT</a>
<b>Horse Power</b>	<a href="#">0.5</a>
<b>Length</b>	<a href="#">Pump Depth 7-1/16"</a>
<b>Phase</b>	<a href="#">3</a>
<b>Voltage</b>	<a href="#">208-230-460</a>
<b>Wetted Material</b>	<a href="#">CAST IRON-304SS-VITON</a>

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

Material: Cast Iron-304SS-Viton | Best Efficiency Point 9 GPM @ 67 FTH | Motor 3/60/208-230-460 Volt, .50 HP | Pump Depth 7-1/16" | Nema Version