

www.pfcstore.com - 763-425-7890 / 800-328-2350



## GRUNDFOS MTR 3-15/15 COOLANT PUMP THREE PHASE-NEMA VERSION

Material: Cast Iron-304SS-Viton |  
Best Efficiency Point 14 GPM @  
375 FTH | Motor 3/60/208-230-460  
Volt, 3 HP | Pump Depth 15.50" |  
Nema Version



**SKU:** 96515422

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Grundfos](#)  
[Coolant/Condensate Pumps](#)

**Model Number** MTR 3-15/15 A-  
WB-A-HUUV

**Part Number** 96515422

## PRODUCT DESCRIPTION

Grundfos MTR pumps are vertical multi and single stage centrifugal pumps designed for pumping of cooling lubricants for machine tools, condensate

www.pfcestore.com - 763-425-7890 / 800-328-2350

transfer and similar applications. All models are designed to be mounted on top of tanks with the pump stack immersed in the pumped liquid.

Heavy-duty, multistage pumps that offer a unique hydraulic design and an unequaled performance range. Cartridge shaft seal and a universal flange system enables rapid replacement and ensures reliability. Special priming screw in allows for liquid levels down to 1 inch (25 mm) and protects against dry running

Product photo could vary from the actual product

**Estimated Delivery is 3 to 4 weeks**

[MTR Specs](#)

[MTR Manual](#)

ADDITIONAL INFORMATION

Weight	90 lbs
Dimensions	50 × 18 × 18 in
Best Efficiency Point	<a href="#">14 GPM @ 375 FTH</a>
Connections	<a href="#">1.25" NPT</a>
Horse Power	<a href="#">3</a>
Length	<a href="#">Pump Depth 15-9/16"</a>
Phase	<a href="#">3</a>
Voltage	<a href="#">208-230-460</a>
Wetted Material	<a href="#">CAST IRON-304SS-VITON</a>